

PLUG-IN → SEMI-VERTICAL MULTIDECKS

Atlanta RDAT-20

BSA




STANDARD FEATURES

- working temperature: from 0°C to 2°C
- refrigerant: R290
- natural defrosting
- automatic evaporation of condensate
- electronic controller with temperature indicator
- exposition: zinc-plated steel, powder coated in white (RAL 9003)
- 3 rows of suspended shelves, on shelves and on air inlet price holders 39 mm
- lighting: top, LEDit, NW-4
- color of the base black (RAL 9005)
- Integrated sidewalls (perspex)
- mechanical night blind



Atlanta RDAT-20 2500 BSA

BSA — low glass or front glass riser | single, straight | fixed



RDAT-20 BSA



AVAILABLE MODULES

0880 1180 1875 2500
0580G

JBG-2 Sp. z o.o. reserves the right to change the standards of devices or to withdraw products without prior notice.

Designation of the energy efficiency class is dedicated to a particular products, which are presented on each page of the catalogue. Indicated energy efficiency class depends on a module type, equipment, glassing version and type of a refrigerant. Amendment of each of the said parameters may cause amendment of the energy efficiency class. Contact the producer to acknowledge the energy efficiency class for the product with different parameters to those presented in the catalogue.