






Hodule:




0600

Available options:

- working temperature straight modules from 2°C to 4°C; corner NZ45 from 2°C to 4°C; corner NZ90 from 4°C to 8°C
- electrical defrosting
- automatic evaporation of condensate
- electronic controller with temperature indicator
- energy saving fans
- exposition: 3 suspended glass shelves + bottom made of powder coated, zinc-coated metal plate
- shelves support and bottom shelf in grey colour RAL 7004
- back doors, sliding, double glazed (in corner and 0600 modules hinged door)
- lighting top and each shelf energy-saving, LEDit, WW-2
- sidewalls integrated with thermopane glass, with screen printing

Elegant RDEL-21 1400 GD

Cross sections:



GDT - glass | double, straight | tilt

Available modules: 0600 0900 1400 NZ45 NZ90

JBG-2 Sp. z o.o. reserves the right to change the standards of devices or to withdraw products without prior notice

Designation of the energy efficiency class is dedicated to a particular products, which are presented on each page of the catalogue. Indicated energy efficiency class depends on a module type, equipment, glassing version and type of a refrigerant. Amendment of each of the said parameters may cause amendment of the energy efficiency class. Contact the producer to acknowledge the energy efficiency class for the product with different parameters to those presented in the catalogue.