



**Refrigerant:** 

R744



## Available options:


Module:

1250

- working temperature straight module and corners from 0°C to 2°C
- electrical defrosting
- electronic expansion valve
- 2 x NTC temperature probe
- siphoned condensate drains
- exposition: zinc-plated steel, powder coated in white (RAL 9003)
- worktop: linen stainless steel
- lighting optionally LEDit (top)
- color of the base black (RAL 9005)
- no PVC floor profiles (optionally)
- without perspex covers (optionally)
- without sidewalls (optionally)
- bumper (optionally)

Grazia LDGR-09 2500 GC

Cross sections:



 $\textbf{GCL} - \textbf{glass} \mid \textbf{single, bent} \mid \textbf{lift up}$ 

Available modules: 1250 1875 2500 3750 NW45 NZ45

JBG-2 Sp. z o.o. reserves the right to change the standards of devices or to withdraw products without prior notice.

Designation of the energy efficiency class is dedicated to a particular products, which are presented on each page of the catalogue. Indicated energy efficiency class depends on a module type, equipment, glassing version and type of a refrigerant. Amendment of each of the said parameters may cause amendment of the energy efficiency class. Contact the producer to acknowledge the energy efficiency class for the product with different parameters to those presented in the catalogue.